

# Certificate of Constancy of Performance



Certificate No.: 0757-CPR-229PANIK-7013137-4-11

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this certificate applies to the construction product

Basis:

EN 1125:2008-01

## Panic exit devices

### Panic exit devices operated by a horizontal bar for single and double leaf doorsets "IQ lock"

Product description/  
specification

According to configuration in **annex 1**

Levels and classes of  
performance

According to configuration in **annex 1**

Intended use(s)

Intended for use on doors in escape routes with requirements for fire resistance and smoke control

placed on the market  
under the name or trade  
mark of

**GEZE GmbH**

Reinhold-Vöster-Str. 21-29, DE-71229 Leonberg

and produced in the  
manufacturing plant(s)

**6039631 + 7013137 + 8003725**

Notified body No.  
EC-Reference-No.

**0757**

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s)



**EN 1125 : 2008**

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the **constancy of performance of the construction product**.

This certificate was first issued on 09.09.2009 and will remain valid until 11.10.2024, as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

The use of this certificate and the marking of the products are bound by an existing certification and surveillance contract with the **ift** Rosenheim no. 229PANIK 7013137.

Christian Kehrer  
Head of notified product certification body  
**ift** Rosenheim  
11.11.2021



[www.ec.europa.eu](http://www.ec.europa.eu)

Identity check



[www.ift-rosenheim.de/ift-zertifiziert](http://www.ift-rosenheim.de/ift-zertifiziert)  
ID: 5C2-92539

# Certificate of constancy of performance

Annex 1 Page 1 of 5  
Certificate holder: GEZE GmbH  
Date of issue: 11.11.2021



Certificate No.: 0757-CPR-229PANIK-7013137-4-11

## Panic exit devices as per EN 1125: 2008 for single and double leaf doorsets: Touch-bar and push-bar operation

For operation type A (push-bar operation)

<b>Classification:</b>	<b>3</b>	<b>7</b>	<b>7</b>	<b>B</b>	<b>1</b>	<b>3</b>	<b>2</b>	<b>1/2</b>	<b>A</b>	<b>A/B</b>
------------------------	----------	----------	----------	----------	----------	----------	----------	------------	----------	------------

For operation type B (touch-bar operation)

<b>Classification:</b>	<b>3</b>	<b>7</b>	<b>7</b>	<b>B</b>	<b>1</b>	<b>3</b>	<b>2</b>	<b>2</b>	<b>B</b>	<b>A/B</b>
------------------------	----------	----------	----------	----------	----------	----------	----------	----------	----------	------------

Intended use: Intended for use on doors in escape routes with requirements for fire protection and smoke control

Test report: No. 207 41089 Rev 1 of 07 January 2010  
Test report: No. 207 36800 of 12 February 2009  
Test report: No. 120001894.11 of 15 December 2006 (MPA)  
Test report: No. 120001894.10 of 15 December 2006 (MPA)  
Test report: No. 10-001639-PR01 of 03 April 2013  
Test report: No. 10-001682-PR01 of 25 July 2013  
Test report: No. 13-000950-PR01 of 24 April 2013  
Test report: No. 271 35385 R2 of 13 August 2009  
Test report: No. 271 38194 of 27 May 2009  
Test report: No. 207 37980 of 17 August 2010  
Test report: No. 13-000685-PR03 of 05 July 2013  
Test report: No. 13-000685-PR04 of 05 July 2013  
Test report: No. 14-003403-PR01 of 04 November 2016  
Test report: No. 14-003403-PR02 of 04 November 2016  
Test report: No. 16-000815-PR01 of 28 July 2016  
Test report: No. 16-000815-PR02 of 04 December 2017  
Test report: No. 17-000792-PR01 of 21 July 2017

# Certificate of constancy of performance

Annex 1 Page 2 of 5  
 Certificate holder: GEZE GmbH  
 Date of issue: 11.11.2021



Certificate No.: 0757-CPR-229PANIK-7013137-4-11

## Panic exit devices:

Function	Designation	Type of device	Backsets	Distance	Face plate	Strike plate	Hole
I	IQ lock M IQ lock M DL	A	35 mm to 100 mm	72 mm to 94 mm	20 mm to 30 mm	Flat strike plate Corner strike plate Flap strike plate	Round cylinder and profile cylinder
I*	IQ lock C IQ lock C DL	A					
II	IQ lock EM IQ lock EM DL	A					
IM	IQ lock EL IQ lock EL DL	A					
IM*	IQ lock AUT	A					

## In combination with:

### Panic exit device:

No.	Designation	Type of device	Backsets	Face plate	Accessory
1.	Strike box DL	A	35 mm to 100 mm	20 mm to 30 mm	133916
					133917
					133918
					133919
					133920
					133921
					133922
					134955
					135799
					153741
					156705
					156709
					156710
					156711
					156712
					156726
					157391
					161530
					161532
					161977
161978					
161980					
162310					
162311					
162322					
162323					
162324					
164102					

# Certificate of constancy of performance

Annex 1 Page 3 of 5  
Certificate holder: GEZE GmbH  
Date of issue: 11.11.2021



Certificate No.: 0757-CPR-229PANIK-7013137-4-11

## Internal hardware furniture:

No.	Manufacturer	Type	Code
1.	GEZE GmbH ***	Panikgriffstange	-/-
2.	ASSA ABLOY (Schweiz) AG***	MSL Art. 5971	-/-
3.	ASSA ABLOY (Schweiz) AG*	e-bar 5980-5983	-/-
4.	HEWI Heinrich Wilke GmbH***	PS160XA10 and PS160XA20	DO 20.13
5.	ECO Schulte GmbH & Co. KG*	EPN 2000	DO 2.17
6.	ECO Schulte GmbH & Co. KG**	EPN 900 III	DO 3.03
7.	GfS-Gesellschaft für Sicherheitstechnik mbH*	70070-71 und 70073-74	-/-
8.	FSB Franz Schneider Brakel GmbH & Co. KG**	77 7980	-/-
9.	WSS Wilh. Schlechtendahl & Söhne GmbH & Co. KG*	01.692.XXX and 01.693.XXX	-/-
10.	ECO Schulte GmbH & Co. KG***	EPN 950	DO 20.01
11.	ECO Schulte GmbH & Co. KG**	EPN 900 IV	DO 20.01
12.	Glutz AG*	56711.00.00.30.CRNI	-/-
13.	Glutz AG***	56721.PZ.92.30.CRNI	-/-
14.	Schüco**	240192	-/-
15.	Schüco**	240195	-/-
16.	Schüco**	240194	-/-
17.	Schüco**	240193	-/-

\*Touch-bar operation

\*\*Push-bar operation projection category 1

\*\*\*Push-bar operation projection category 2

# Certificate of constancy of performance

Annex 1                      Page 4 of 5  
 Certificate holder: GEZE GmbH  
 Date of issue:              11.11.2021



Certificate No.: 0757-CPR-229PANIK-7013137-4-11

## External hardware furniture:

No.	Manufacturer	Type	Code
1.	FSB Franz Schneider Brakel GmbH & Co. KG	-/-	DO 20.3.01 DO 20.3.02 DO 20.3
2.	HOPPE Holding AG	-/-	DO 20.5.01 DO 20.5.02 DO 20.7.01 DO 20.7.02 DO 20.20.01 DO 20.20.02
3.	HEWI Heinrich Wilke GmbH	162XAH11.530, 162XAH52.640, 111XAR11.110, 111R11.210, 111R11.230, 111R11.240	DO 20.13
4.	Grundmann Beschläge GmbH	1554FHA, 1754FHA, 2254FHA, 2454FHA, 2554NFHA	-/-
5.	ECO Schulte GmbH & Co. KG	D-116.AL, D-116.ER, D-335.ER	DO 20.01.01
6.	KABA AG	elologic c-lever	-/-
7.	ASSA ABLOY (Schweiz) AG	-/-	5974 5978 5979
8.	Süd-Metall Beschläge GmbH	Paula-R FS	-/-
9.	Hermet Metallwaren GmbH	1801, 1801.FS, 1801.GK, 1801 R.FS, 1805; 1808, 1808.FS, 1808.GK, 1809, 1811, 1816	ift 235 8000244
10.	VIELER International KG	-/-	DO 20.12.01 DO 20.12.02

# Certificate of constancy of performance

Annex 1                      Page 5 of 5  
Certificate holder: GEZE GmbH  
Date of issue:              11.11.2021



Certificate No.: 0757-CPR-229PANIK-7013137-4-11

## Explanations:

Description:	Automatic, during closing, self-locking mortise locks with escape door function (panic function) and split cross latch. The bolt is located at the centre between the two latch parts.
Function I:	Solid lock follower, continuous escape door function from inside. Opening from inside is always possible using the internal hardware. Opening from outside is possible with action of the key on the latchbolt.  *with additional monitoring contacts integrated in the lock
Function II:	Split lock follower, continuous escape door function from inside. Opening from inside is always possible using the internal hardware. The external hardware, and/or the external follower part are engaged and disengaged by electronic control. Special hardware with a split bolt is required.
Function IM:	Solid lock follower, continuous escape door function from inside. Opening from inside is always possible using the internal hardware. Opening from outside is possible with action of the key on the latchbolt. Motorised bolt drive.  *motor-driven unlocking function of active leaf and inactive leaf
Locking cylinder	Use of any type of locking cylinder with free turn facility does not have any effect on due operation.