

Product data sheet

Guide rail TS 1500 G/F

*



with mechanical hold-open device and lever

AREAS OF APPLICATION

- Single leaf doors
- Installation on the hinge or opposite hinge side (only limited door leaf thicknesses)
- Right and left single-action doors
- To hold open non-fire protection doors

PRODUCT FEATURES

→ Quick installation due to clip-on slide block

TECHNICAL DATA

Productname	Guide rail TS 1500 G/F *
Length	390 mm
Width	30.5 mm
Height	20.5 mm
opening restrictor upgradable	Yes
Hold-open function	Mechanical
Hold-open device can be overridden	Yes
Hold-open range	80 ° - 130 °
Smoke switch integrated	No

VARIANTS / ORDER INFO

Designation	Description	Ident-No.	Colour	Dimensions	Hold-open point min.
Guide rail TS 1500 G/F	with mechanical hold-open device and lever	101889	silver-coloured	390 x 30.5 x 20.5 mm	80 °
Guide rail TS 1500 G/F	with mechanical hold-open device and lever	101892	according to RAL	390 x 30.5 x 20.5 mm	80 °
Guide rail TS 1500 G/F	with mechanical hold-open device and lever	101891	white RAL 9016	390 x 30.5 x 20.5 mm	80 °

ACCESSORIES

FLEXIBLE OPENING RESTRICTOR

for riveted guide rail, standard guide rail BG, standard guide rail and Boxer 20.7 mm guide rail



Designation	Description	Ident-No.
Flexible opening restrictor	for riveted guide rail, standard guide rail BG, standard guide rail and Boxer 20.7 mm guide rail	069780

Guide rail TS 1500 G/F *



INSTALLATION MATERIAL

MOUNTING PLATE GUIDE RAIL *

For TS 1500 G



Designation	Description	Ident-No.	Colour
Mounting plate guide rail	For TS 1500 G	072355	according to RAL
Mounting plate guide rail	For TS 1500 G	072333	silver-coloured

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.